

HD-SDI Box Camera

DH-8770



Features

- | | |
|--|--|
| ● 2M SONY CMOS Sensor | ● HLC (High Light Compensation) |
| ● HD-SDI output and analog CVBS output | ● 8 Privacy zones (Each zone size can be modified) |
| ● Support HD-SDI (1920x1080@30P/ 1280X720@60P) | ● Digital Zoom (x64) & PIP(Full/Zoom Image) |
| ● ACCE (D-WDR) | ● Flicker Suppression |
| ● Support 2DNR / 3DNR | ● Low Shutter Control |
| ● OSD function control | ● Motion Detection |
| ● DPC (Dead Pixel Correction) | ● DEFOG |

Specifications

Image Device	Image Sensor	SONY 1/2.8" 2 Mega-Pixel CMOS Sensor
	Resolution	FULL HD (1920x1080@30FPS / 1280X720@60FPS)
Lens	Mount	C/CS mount
	Lens control	DC / Auto iris
Functions	AGC	Low / Middle / High
	Shutter	1/25(30)~1/50000
	Sens-Up	x2~x30
	Min Luminance	0.1 Lux (Color) / 0.05 Lux (B/W) / 0.02Lux(Sens-up x30)
	White Balance	ATW / Manual / INDOOR / OUTDOOR / AWC→SET
	Backlight Compensation	BLC / HSBLC / Off
	D-WDR	Low / Middle / High (ACCE) / Off
	2D/3D-NR	2DNR / 3DNR / SMART NR
	Adjust	SHARPNESS / MONITOR / LSC / NTSC/PAL
	Privacy zone	On / Off (8 Zone Selectable)
	Digital Zoom / PIP	On / Off(x2 ~ x64)
	Day & Night	Color / B&W / Auto / EXT@IR-Smart control
	OSD	English/Japanese / Traditional /Simplified
Others	Motion Detection , Image Flip & Mirror	
Video Output	HD-SDI	MCX connector
	Analog CVBS	CVBS output through BNC
Electricity	Power Consumption	DC12V / 300mA
Mechanical	Dimension	121.6 (D) x 63 (W) x 54 (H) mm
	Weight	250g (DC) / 360g (AC)
Environment	Operation Temperature	0°C ~ 50°C

OSD Feature

1.LENS	DC	INDOOR / OUTDOOR		
	VIDEO			
	MANUAL			
2.EXPOSURE	SHUTTER	Auto / (x2~x30) / FLK / (1/30~1/50000)		
	AGC	Low / Middle / High		
	SENS-UP	Off / ,Auto		
	BRIGHTNESS	1-100		
	ACCE	Off / Low / Middle / High		
	DEFOG	Off / Low / Middle / High		
	BACKLIGHT	Off		
		BLC	GAIN	Low / Middle / High
			AREA	POSITION
				SIZE
			DEFAULT	
		HSBLC	SELECT	AREA1 / AREA2 / AREA3 / AREA4
			DISPLAY	ON / OFF
LEVEL			0-100	
MODE			DAY / NIGHT	
BLACK MASK			ON / OFF	
DEFAULT				
3.WHITE BAL	ATW			
	MANUAL	Blue(0-100)		
		Red(0-100)		
	INDOOR			
	OUTDOOR			
	AWC→SET			
4.DAY&NIGHT	AUTO	DELAY	0-60(sec)	
		D→N(AGC)	0-100	
		N→D(AGC)	0-100	

	COLOR				
	B/W	BURST	ON / OFF		
		IR SMART	LEVEL(0-15)		
			AREA		
		IR LED	ON / OFF		
		IR PWM	0-100		
	EXT				
5.NR	2DNR	ON / OFF			
	3DNR	ON	S-LEVEL(0-100)		
			E-LEVEL(0-100)		
		OFF			
	LEVEL	0-100			
	SMART NR				
6.SPECIAL	CAM TITLE	ON / OFF			
	D-EFFECT	FREEZE	ON / OFF		
		MIRROR	OFF / MIRROR / V-FLIP / ROTATE		
		D-ZOOM	ON	PIP	ON / OFF
			D-ZOOM	x2 - x64	
			PAN&TILT		
			DEFAULT		
		NEG IMAGE	ON / OFF		
	MOTION	ON	SELECT	AREA1 / AREA2 / AREA3	
			DISPLAY	ON / OFF	
			SENSITIVITY	0-60	
			MOTION VIEW	ON / OFF	
			DEFAULT		
OFF					
PRIVACY	ON	SELECT	AREA1 – AREA8		
		DISPLAY	ON / OFF		
		COLOR	1-16		

		DEFAULT		
		OFF		
	LANGUAGE	ENG / JPN / CHN1 / CHN2		
	DEFECT	LIVE DPC	ON / OFF / AUTO	
		LEVEL	0-60	
		STATIC DPC	ON / OFF	
		START		
		LEVEL	0-60	
		SENS-UP	x2 - x30	
	RS485	CAM ID	0-255	
		ID DISPLAY	ON / OFF	
		BAUDRATE		
		VERSION		
7.AJUST	SHARPNESS	SHARPNESS	ON / OFF	
		LEVEL	0-100	
		RESOLUTION	ON / OFF	
	MONITOR	LCD	GAMMA	AUTO
				USER1
				USER2
				0.45 - 1.00
				BLUE GAIN(0-100)
				RED GAIN(0-100)
		CRT		BLACK LEVEL
				BLUE GAIN(0-100)
				RED GAIN(0-100)
		OSD	TEXT COLOR	1-8
			OUTLINE	ON / OFF
			LSC	ON / OFF
			NTSC / PAL	
		8.RESET		