

Dome Camera

High Resolution Dome Camera

HS-CD3293/HS-CD3297



HS-CD3293




HS-CD3297

- 700 TVL High Resolution Camera.
- 3 Axis Camera Mechanism Adjustment Design.
- 21 IR LED for an Effective 15M Viewing Distance.(HS-CD3297)
- Electronic Day-and-Night Color/Mono Switching.
- Low Power Consumption Prolongs Product Liability.
- Solid and Compact Aluminum Die-Casting for Vandal Proof.
- Support both Side and Top Cable Wiring Method.
- Optional Wall Fixation Bracket and Cable Management.
- Class IP-65 Weatherproof Function.
- RoHS and WEEE Compliance.


Specifications

Model	HS-CD3293	HS-CD3297
Pick up device	1/3" SONY Super HAD CCD 1/3" SONY Super HAD CCD II	
Total Pixels	NTSC:1028(H) x 508(V) / PAL:1028(H) x 596(V)	
Effective Pixels	NTSC:976(H) x 494(V) / PAL:976(H) x 582(V)	
Resolution	700 TV lines	
Lens mechanism	3 Axis	
Synchronization	Internal	
Scanning System	2:1 Interlace	
S/N Ratio	More than 50 dB (AGC OFF)	
Electronic Shutter	Auto : 1/60 (1/50) ~ 1/100,000 sec	
Min. Illumination	0.1 Lux / F2.0 (50IRE)	
Video Output	1.0Vp-p / 75 ohm composite	
AGC	Auto	
AWB	Auto	
Day & Night	Auto	External
Smart IR	N/A	Auto
OSD Control	Pelco C	
Lens Type	Board Lens : 3.6mm / F2.0	Vari Focal Lens : 2.8~12mm / F1.2
IR distance	N/A	15M (21pcs IR LED)
IR Trigger	N/A	7 Lux±3 Lux IR ON/OFF
Power Source	DC12V±10% / 1A	
Power Consumption	1.2W (Max)	3.8W (Max)
Current	120mA (Max)	300mA (Max)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)	
Dimension	80.2(H) x 110(D)mm	99.6(H) x 140(D)mm
Weight	N.W./G.W : 0.44kg / 0.32kg	N.W./G.W : 0.9kg / 0.72kg
Weatherproof	IP65	

Dimension Unit : mm



HS-CD3293



HS-CD3297

