

Hi Resolution Day & Night Speed Dome

IITEC

Model: SPD9530

- ❖ DAY & NIGHT Camera
- ❖ Sony EX-View CCD
- ❖ High Resolution , 530TVL
- ❖ High Speed Operation
- ❖ Outdoor use, IP66
- ❖ Multi-protocol



Specifications

Model No.	Model: SPD7540	
	Indoor dome	Outdoor dome
Effective Pixels	752(H) x 582(V)	
Image Device	1/4" EX-View CCD	
Lens	f = 3.4mm ~ 112.4 mm	
Zoom ratio	Optical: 36X	
IRIS Control	DC IRIS	
Sync. System	Internal/External	
Horizontal Resolution	530 TV Lines	
Minimum Illumination	0 lu x	
Video Output Signal	1Vp-p Composite (75Ω)	
Day & Night	Day / Night / Auto	
Auto Gain Control	Off / Low / Medium / High	
Effective IR	80m ~ 100m	

Electronic Shutter	1/60 ~1/90,000	
White Balance	Auto / ATW/ ONE PUSH / Manual(1800 °k ~ 10,500 °k)	
Electronic Sensitivity	OFF /Auto (x2, x3, x4,.....x 128)	
Pan range	360°Continue	
Tilt range	0°~90° Flip	
Manual speed Pan	0.1~100°/Sec	
Manual speed Tilt	0.1~120°/Sec	
Preset speed	120°/Sec	
Preset accuracy	±0.10°	
Minimum adjustable angle	0.0173° (Manual:0.1°/S)	
Preset points	128 Points	
Access time	0.5 second maximum preset recall time	
Function display	Yes	
Operation return function	Yes	
Vector scan groups (Tour)	6 Programable(Dwell time speed preset point and embed other vector scan or PTZ tours)	
Integrate multi-protocol	Pelco_D/P etc	
Auto Scan	with Smart Programable variable speed	
Long-focus speed-limited	Yes	
Intelligent power off real time memory	Yes	
Home position	Yes	
Camera menu operation	Yes	
IP66 for outdoor use	No	Yes
Operating Temperature	0℃~50℃	-30℃~60℃
Humidity	0%~90% (Non condensing)	
Heater in operation	No	6℃ on 14℃ off
Power	24VAC 2A 60Hz/50Hz	
Consumption	20W	35W
communication	RS485 (+/-) Baud rate:2400~19200bps	
Connection	BNC cable	
Certification	FCC, CE, ROHS, IP66	
Material of dome bubble	Acrylic	
Color of dome bubble	Clear	